

Electrostatic Cling Stock.

Product

Tacky Dry Toner

Brand

Ball & Doggett

Website

www.ballanddoggett.com.au

Product Description

A synthetic, highly durable, repositionable adhesive sheet optimised for high-heat dry toner printing as well as other print methods. Designed for easy application to smooth, non-porous surfaces (glass, plastic, painted metal) and engineered to resist shrinkage, distortion, and melting under printing and environmental stress.

Features

- High heat resistance: suitable for laser/toner, flexo, offset, and screen printing.
- Premium, extra smooth surface for vivid, high-quality print results.
- Durable and conformable for long-term indoor/outdoor exposure.
- Resistant to alcohol, selected solvents, and detergents.
- Does not shrink, distort, or melt under demanding use or high heat.

Applications

- Window graphics and signage (retail, vehicles, restaurants, delis)
- Bumper stickers and laptop skins
- Shelving and storage labels
- Menus, wall graphics, calendars
- Store signage
- Any smooth, non-porous surface requiring repositionable adhesion

Not Recommended For

- Porous or highly textured substrates
- Applications requiring permanent adhesion
- Surfaces exposed to aggressive solvents

Technical Specifications

Total Weight	290 g/m ²
Film Face	91.44 ums
Total Thickness	297.18 ums
Stiffness MD	12±2 mg
Stiffness CD	9±2 mg
Opacity	93%
Tear Strength MD	310±50 grams
Tear Strength CD	322±50 grams